TECHNICAL SPECIFICATION



Stealth™ 8000

Clear K Rated / ASA790-161-300



DESCRIPTION

A lightweight safety spectacle, weighing just 26g, the wraparound 9 base curve polycarbonate lens has a built in adjustable PVC nosepiece for added comfort and stability. Low profile tension control temples provide extra grip. Temple tips feature spectacle cord attachment points. UVA, UVB and UVC protection.

OPTIONS

Clear K & N AS/AF Rated (ASA790-1A1-300)

Clear Anti-mist / Anti-scratch Lens (ASA790-151-300)

Clear K Rated (ASA790-161-300)

Indoor/Outdoor Anti Scratch HC Lens (ASA790-162-900)

Amber K Rated (ASA790-161-200)

Smoke K Rated (ASA790-166-400)

LED Clear Anti-mist Lens (ASA106-121-300)

SAFETY STANDARDS

EN 166







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



Product Weight

26g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)

1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Т



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacturer's Trademark

JSP Dagger



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s $^{\circ}$ Maximum protection for glasses

F



Resistance to Surface Damage by Fine Particles (optional)

Κ

FEATURES



Comfort & Grip

Built-in soft rubber provides both comfort and grip to the side of the head to keep them secure without irritation.



Spectacle Cord Anchor

The temple tips have a spectacle cord anchor point for further practicality, preventing loss or scratching from being put on rough surfaces.



Comfortable Nose Bridge

Built-in adjustable PVC nose piece for added comfort and stability. It flexes and adjusts to fit the shape of the nose.

RANGE



DOWNLOADS



doc-stealth-8000-spectacles.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





